


A3pci1546

2ch Ethernet Board



Features

- 3U size Compact PCI board with a 2-channel 100Base-TX/10Base-T compatible Ethernet functions
- Can be used when adding Ethernet ports
- Equipped with two Intel 82559ER controllers
- HotSwap capability
- Device driver for VxWorks provided (paid option)
- Intel device driver can be used for Windows OS

Models

- A3pci1546: 2-channel Fast Ethernet board
- A3pci1546-VX-PPC: Device driver for PowerPC604/750
- A3pci1546-VX-405: Device driver for PowerPC405GP

Specifications

Ethernet

- Controller : Two Intel 82559ER controllers
- Transmission speed : 10Mbps, 100Mbps (Duplex operation possible for both)
- Connector : Two RJ-45 connectors
- Indicators : Link indicator LED, Activity indicator LED, Speed indicator LED, HotSwap status indicator LED

Bus interface

- Bus : 32-bit 33MHz CompactPCI bus
- Signaling voltage : 3.3/5V (supports both voltages)
- HotSwap : Full Hot Swap capability
- Power requirements : 5V

Board size

- 3U single slot width 160mm x 100mm x 20mm (excluding protrusions)



HUMAN ELECTRONICS

Advanet Inc.

www.advanet.co.jp

Note: The following specifications and product appearance are subject to change for enhancement without notice.



ISO9001

Certification: No.4016-1995-AQ-K0B-Rv4

ISO14001

Certification: No. EMSC-1426

Headquarters 616-4, Tanaka, Okayama 700-0951 JAPAN
TEL +81-86-245-2861 FAX +81-86-245-2860
Tokyo Branch 3F, Hayakawa No.3 Building, 2-2Kanda-Tacho, Chiyoda-ku, Tokyo 101-0046 JAPAN
TEL +81-3-5294-1731 FAX +81-3-5294-1734