

## CPU-162-22 Development Kit



### FEATURES

**COM Express Launchpad** - A COM Express Type 6 Development Kit that provides a complete platform for development, validation and testing of the CPU-162-22

**All Inclusive** - Bundles one COM Express module, one microATX carrier board and a complete set of cables and accessories, including the operating system preinstalled on an SSD drive

**Rugged and Performant** - The CPU-162-22 supports wide operating temperature (-40 to +85°C) and it is powered by Intel Core i7, i5, i3 and Celeron CPUs, up to four cores

**Feature Rich** - Provides a carrier board with plenty of interfaces, including triple display, six PCIe x1 slots, one PEG slot, two Mini PCIe sockets, and four SATA 3.0 ports

**Professional Services** - Constitutes the first step for Eurotech Professional Services, that range from carrier board development to complete system design, certification and manufacturing

The CPU-162-22 Development Kit allows a quick development and prototyping of embedded applications on a pre-validated platform which brings out a rich set of the module functionalities. The kit targets all aspects of an embedded application from hardware interfacing to development of on-board software.

Compliant with PICMG COM Express R2.1 Type 6, the CPU-162-22 is a 95x125mm (Basic) form factor module based on the 6<sup>th</sup> Generation Intel Core processor family (i7, i5, i3 and Celeron), up to four cores and up to 32GB SO-DIMM RAM.

Other features include high speed interfaces: one Gbit Ethernet, four SATA 3.0 with RAID support, four USB 3.0 and eight USB 2.0, eight and sixteen PCIe Gen 3 lanes, and three independent video ports (LVDS, VGA and DDI supporting up to 4096x2304@60Hz).

The CPU-162-22 is a solid building block for projects where reliability in harsh conditions is mandatory, and long term availability is a must, thanks to an operating temperature of -40 to +85°C, support for RAID 0/1/5/10, optional conformal coating and long term support/lifecycle programs.

# CPU-162-22 Development Kit

## Specifications

## Embedded Board Development Kit

Ordering code: CPU-162-22-XX-DK01			
XX		- 02	- 03
PROCESSOR	CPU	Core i5 6442EQ 1.9GHz (2.7GHz), 4 Cores	Core i7 6822EQ 2.0GHz (2.8GHz), 4 Cores
MEMORY	RAM	2x SODIMM Sockets - Up to 32GB DDR4 2133MHz - Dual Channel	
STORAGE	SATA	4x SATA 3.0 (up to 6Gb/s)	
I/O INTERFACES	Ethernet	1x 10/100/1000Mbps - RJ45	
	USB	4x USB 2.0/3.0, 4x USB 2.0 - Type A	
	Serial	2x UART (TX/RX) - Header 4x RS-232 (9 Wires) - Header	
	Video	Triple Independent Displays 1x LVDS <sup>§</sup> - Header 1x VGA - Header 2x DisplayPort	
	Audio	HD Audio 1x Line-In, 1x Line-out, 1x Mic-in - 3.5mm Jack 1x Front Audio - Header 1x S/PDIF - Header	
	PCI Express	1x PCIe x16 (Gen 3) Slot 6x PCIe x1 (Gen 3) Slots 2x Full/Half Size Mini PCIe Slots (PCIe Signal Only)	
OTHER	RTC	Yes (Lithium 3V 210mAh Battery)	
	Fan Conn.	1x CPU Fan, 1x System Fan	
	LEDs	1x SATA Activity, 1x Debug	
	Buttons	1x Power-on, 1x Reset	
POWER	Input	12V (DC-in, Screw-lock Jack)	

For more specifications and certifications, please check the CPU-162-22 datasheet

PRE-INSTALLED SOFTWARE	
OS	CentOS 7

INCLUDED ACCESSORIES		
CARRIER BOARD		CAR-363-13 Micro ATX COM Express Carrier Board
MEMORY	RAM	2x 4GB DDR4 SODIMM Modules
STORAGE	SSD	1x 2.5" 64GB SATA SSD MLC
I/O INTERFACES	SATA	3x SATA 3.0 Data Cables 1x SATA Power Cable
	Serial	1x LPC to Serial RS-232 Expansion Module 4x Serial DB9 Male Cables
	Video	1x DP Male to HDMI Female Adapter 1x VGA Cable
POWER SUPPLY	DC-DC PSU	1x 150W DC-DC ATX Power Supply Unit
	AC-DC PSU	1x 100W 100/240VAC-in 12VDC-out (Jack Conn. with Screw) Level VI Power Supply Unit
	Cables	3x Power Cables (US, JP, EU, UK)
OTHER	Heatsink	1x Heatsink with Fan

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies. § LVDS Support requires BIOS customization.