ACS-9110-00

GSM TRI-BAND ANTENNA KIT

Kit Contents

- 1x GSM Tri-Band Antenna with Female SMA connector
- 1x 7040000036L: Female MCX to Female SMA adaptor cable for use with the COM-1288 & COM-1289



704000036L


Module	Connector
COM-1288	GPRS
COM-1289	J5

System	Connector
DuraCOR/ Alphabox	Not Required
DuraNAV/ AVL-Light	Not Required

Connectors

- 1x Male MCX to COM module
- 1x Female SMA to Antenna (Cn1)

Mechanical Dimensions




All dimensions in millimetres

GSM Tri-Band Antenna

Module	Connector	Sys
COM-1288	704000036L, Female SMA	Dura Alpha
COM-1289	704000036L, Female SMA	Dura AVL-

System	Connector
DuraCOR/ Alphabox	A2
DuraNAV/ AVL-Light	A2

Mechanical Dimensions



Specifications

Characteristic	Typical
Frequency Range 1	896 ~ 960 MHz
Frequency Range 2	1710 ~ 1990 MHz
Impedance	50 Ohms
VSWR	1:1.5
Gain	4.15 dBi
Polarization Form	Vertical
Radiation	Directional
Maximum Power	20 Watts
Lightning Protection	DC Grounding
Fixing	Self adhesive strip on lower surface



EuroTec H SpA

a member of the Eurotech Group Via Fratelli Solari, 3/a 33020 Amaro (UD) - Italy E-mail: sales@ eurotech.com Tel. +39 0433 485 411 - Fax. +39 0433 485 499

www.eurotech.com

DIGITAL TECHNOLOGIES FOR A BETTER WORLD

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EuroTecH S.p.A. While reasonable precautions have been taken, EuroTecH S.p.A. assumes no responsibility for any error that may appear in this document.

All trademarks or registered trademarks are the properties of their respective companies.