

PRELIMINARY DATA SHEET

EUROTECH - 6.5" Rugged Display

Rugged Military/Avionics Flat Panel Display

FEATURES

COLOR AMLCD:

- 6.5" TFT LCD with LED Backlight

RESOLUTION:

- VGA Resolution – 640 x 480 pixels

TOUCHSCREEN:

- Resistive Film Touchscreen Controller

BUTTONS:

- 6 pushbuttons

CHASSIS:

- Hardened Aluminum Chassis with Gasketing for Water Resistance and EMI Protection

PROTECTIVE WINDOW:

- Protective Window for Explosive Decompression
- ITO (optional), Anti-Reflective and Hard Coatings

MOUNTING:

- Bracket Mountable, Rear Panel Hole Pattern

CUSTOM OPTIONS:

- Environments Certifications, Integrated CPU



DESCRIPTION

The Eurotech Display is a rugged flat panel 6.5 inches TFT Liquid Crystal Display. this hardened military/avionics-grade monitor features daylight readability, lightweight aluminum chassis, and anti-glare protective covers for impact protection and explosive decompression. Designed to meet military GAM EG13 environmental standards, this rugged Commercial Off the Shelf (COTS) flat panel incorporates a hardened mechanical design well suited for avionics, vehicular, and other high reliability applications.

The 6.5" display features a high luminance LED backlight for long lamp life, excellent dimming capabilities (down to 4%), and exceptional low-temperature operation (-40°C). The unit features 6 front bezel buttons for brightness controls and accepts standard VGA.

Optimized for panel-mount ship, vehicle and airborne installations, the display integrates a resistive touchscreen with VGA input and RS-422 touchscreen controller.

SPECIFICATIONS

LIQUID CRYSTAL DISPLAY:

- 6.5" a-SI TFT LCD with LED Backlight

LUMINANCE:

- 850 cd/m² (nit) typical

VIDEO INPUT:

- VGA Video Input

RESOLUTION:

- VGA Resolution – 640 x 480 pixels

TOUCHSCREEN:

- Resistive Film Analog Controller, RS-422 Interface
- WinCE / WinXP / Linux / DOS drivers

BUTTONS:

- 3 Pushbuttons for Brightness
- 3 Configurable Pushbuttons

VIEWING ANGLE:

- -50~50° (H), -35~45° (V) at contrast ratio 10:1

PROTECTIVE WINDOW / COATINGS:

- Anti-reflective, ITO (optional) Hard Coatings

LAMP LIFE (MTBF):

- 50,000 Hours

WEIGHT:

- Approx. 3.0 lbs
- Approx. 1.36 kg

EMI / EMC AND ENVIRONMENTAL COMPLIANCE:

- Designed to meet GAM EG13 standards

POWER INPUT:

- 18 to 36 Vdc

OPERATING TEMPERATURE:

- -40 °C to +60 °C
- -40 °F to +140 °F

FINISH:

- Black Anodized Finish

COOLING:

- Not required (natural convection)

PHYSICAL DIMENSIONS:

- 192.5 mm (W) x 136 mm (H) x 40 mm (D)
- 7.56" (W) x 6.36" (H) x 1.57" (D)