



- Integrated 3G Cellular
- Wi-Fi, GPS and Zigbee Options
- Truly Industrial
- IoT Ready
- Ready to Deploy
- Open Platform
- Cloud Ready

## Features

**Connected** - With integrated support for Cellular, Wi-Fi, GPS, and 802.15.4/Zigbee, the ReliaGATE 20-11 provides a powerful combination of interfaces for a broad range of communication connectivity applications.

**Truly Industrial** - Extended temperature operation and protected power supply give industrial strength to the ReliaGATE 20-11.

**IoT Ready** - Ideally suited for IoT applications to connect sensors, actuators and devices to the business enterprise.

**Ready to Deploy** - Includes a powerful network routing software application that provides simple web based configuration tool to deploy for IoT and network applications.

**Open Platform** - Provides a Java/OSGi gateway middleware, to free the developer from proprietary solutions

**Cloud Ready** - Enjoy the benefits of the Everyware Cloud (EC) end-to-end solution by collecting, controlling, transporting, and analyzing data from the field, regardless of how big your domain is; whether it is a building, a campus, a city, a country or the world.

## Description

The ReliaGATE 20-11 is a ready-to-deploy industrial grade Multi-service IoT Edge Gateway that enables communications, computation power, simplified application deployment and IoT platform integration.

The ReliaGATE 20-11 provides a flexible communication architecture that includes a 2G/3G cellular, Wi-Fi, 802.15.4/Zigbee and GPS interfaces. It offers connectivity to a wide range of sensors and edge devices and makes it easy to deliver the data to business applications. The ReliaGATE 20-11 also includes interfaces for wired connectivity such as Gigabit Ethernet, up to two serial ports and two USB ports.

The ReliaGATE 20-11 is simple to manage and delivers out-of-the-box connectivity and intuitive configuration of the routing parameters thanks to a web GUI and over-the-air options.

The ReliaGATE 20-11 is [Everyware Software Framework \(ESF\)](#) ready. ESF is a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/ OSGi middleware for IoT gateways.

Distributed and supported by Eurotech, ESF adds advanced security, diagnostics, provisioning and remote access. It supports ready-to-use field protocols (including Modbus, OPC-UA, S7), MQTT connectivity, web-based visual data flow programming and deep configuration.

ESF is also integrated with [Everyware Cloud \(EC\)](#), [Eurotech IoT Integration Platform](#) (separately available), enabling advanced diagnostics, provisioning, and full remote device access and management.

| Specifications          |                   |   |
|-------------------------|-------------------|---|
| <b>PROCESSOR</b>        | CPU               | Atom E620 (T) 600MHz – E640(T) 1GHz – E660(T) 1.3GHz – E680(T) 1.6GHz   |
| <b>MEMORY</b>           | RAM               | 512MB 800MHz DDR (up to 2GB Optional)   |
| <b>STORAGE</b>          | SATA              | 8GB Half SATA SSD (up to 256GB Optional) or SD/MMC Extended Memory  |
| <b>I/O INTERFACES</b>   | Ethernet          | 1x 10/100/1000Mbps - RJ45   |
|                         | USB               | 2x Host 2.0 - Type A  |
|                         | Serial            | 1x RS-232/422/485 – 1x RS-232/485   |
|                         | CAN               | 1x CAN bus  |
|                         | Digital I/O       | 6x GPIO and Alarm Buzzer  |
|                         | Video             | 1x VGA – 1x LVDS (Optional Internal)  |
|                         | Audio             | 1x Headphone, 1 x MIC   |
| <b>RADIO INTERFACES</b> | Cellular          | Internal UMTS/HSPA+ or CDMA/EvDO Modem  |
|                         | GPS               | Yes, Integrated   |
|                         | Wi-Fi             | a/b/g/n/- Access Point & Client   |
|                         | 802.15.4 / Zigbee | Factory Option  |
| <b>OTHER</b>            | LEDs              | 1x Power, 3x miniPCle Slot, 2x Programmable (Dual Color Green/Amber)  |
|                         | Buttons           | 1x Reset, 1x Programmable   |
| <b>POWER</b>            | Input             | 9 - 36VDC (Nominal 12 or 24VDC)   |
|                         | Consumption       | 6W (Pulse 8W), Sleep 2W (without 3G, GPS, Zigbee, WLAN)   |
| <b>ENVIRONMENT</b>      | Operating Temp    | - 20 to +70°C (Option: - 40 to +80°C)   |
|                         | Storage Temp      | - 40 to +85°C   |
|                         | Humidity          | 5-95% RH @25-35°C Non-condensing  |
| <b>CERTIFICATIONS</b>   | Regulatory        | CE, FCC Class A, ISED   |
|                         | Safety            | UL 60950 Carrier Approved   |
|                         | Environmental     | RoHS2, REACH  |
|                         | Wi-Fi / BT Radio  | CE, FCC Class A, ISED   |
|                         | Cellular Radio    | Verizon   |
| <b>MECHANICAL</b>       | Dimensions        | 5.44"x4"x2" / 138x102x52mm (Box) – With Installed Brackets: 6.3"x4"x2" / 160x102x52mm   |
| <b>SOFTWARE</b>         | OS                | Linux and Windows Support   |
|                         | Routing           | Static Routes, DHCP, DNS Client, Firewalling, SECURITY AES, 3DES, SSH, Isec, NAT (Network Address Translation), Terminal Server & Client, Port Forwarding |