



- Automotive Grade (E-Mark, SAE/J1455)
- Internal LTE Cat 1 (NA, EU, JP)
- Rugged
- Internal UPS
- ARM® Powered
- Customizable



## Features

**Automotive Grade** - E-Mark and SAE/J1455 certifications, GPS with Dead Reckoning, 6-32V power supply with ignition sense, surge, noise, reverse polarity, overvoltage and short protection

**Internal LTE Cat 1 (NA, EU, JP)** - Carrier certified LTE Cat 1 cellular modem with European, North American and Japanese variants, ready for immediate deployment

**Rugged** - IP67 ingress protection with rugged connectors, wide operating temperature range and a sturdy metal enclosure

**Internal UPS** - Includes a rechargeable internal 2000mA/h UPS to provide up to 5 minutes of operation and safe shutdown

**ARM Powered** - Powered by NXP i.MX 6UltraLite CPU to deliver performance and power efficiency

**Customizable** - Personalization and full customization options are available, ranging from branding ("skins" and color) to deep HW/SW configurations

## Description

The DynaGATE 10-06 is a Multi-service IoT Edge Gateway that has been designed to deliver LTE connectivity with 2/3G fallback to automotive and rugged applications.

Based on the NXP i.MX 6UltraLite Cortex-A7 processor family, with 512MB of RAM, 4GB of eMMC and a user-accessible microSD slot, the DynaGATE 10-06 is a low power gateway suitable for demanding use cases: it supports a 6 to 36V power supply with protections and vehicle ignition sense, two protected RS-232/RS-485 serial ports, two CAN bus interfaces, one noise and surge protected USB port, and two protected digital interfaces.

The DynaGATE 10-06 features a wide range of connectivity capabilities: it integrates an internal LTE Cat 1 cellular modem with dual Micro-SIM support, Wi-Fi, Bluetooth Low Energy, a dedicated GPS with Dead Reckoning and two Fast Ethernet ports.

A rechargeable internal 2000mA/h battery provides uninterrupted operation for up to 5 minutes in the event of power failure and permits a safe shutdown.

The unit complies with popular automotive certifications, such as E-Mark, and optionally SAE/J1455 ensuring reliable operation even in the harshest conditions with IP67 ingress protection, wide operating temperature range and rugged connectors (AMPSEAL and M12).

### Ordering code: DYGATE-10-06-XX

XX		- 21	- 22	- 23	- 24	- 25	- 26	- 27
PROCESSOR	CPU	i.MX 6Ultralite, 696MHz, Single Core						
MEMORY	RAM	512MB DDR3L						
STORAGE	Embedded	4GB eMMC						
	Other	1x microSD Slot (User Accessible)						
I/O INTERFACES	Ethernet	2x 10/100Mbps on M12						
	USB	1x Host 2.0 (Noise and Surge Protected) - Type A (User Accessible), 1x Host 2.0 OTG (Noise and Surge Protected) - Micro AB (User Accessible)						
	Serial	1x RS-232, 1x RS-485 (Three-wire, Non-isolated, Surge Protected, RS-485 Termination and Fail-safe Resistors) – 1x Serial Console TTL (User Accessible)						
	CAN 2.0B	2x CAN bus (Non-isolated)						
	Digital I/O	1x Ignition Key Input, Surge Protected, 1x Isolated Digital Input, 1x Isolated Digital Output, 1x Odometer Input, 1x Isolate Forward Input						
RADIO INTERFACES	Cellular	No			LTE Cat 1 (NA)	LTE Cat 1 (NA) 3G Fallback	LTE Cat 1 (EU) 2G Fallback	LTE Cat 1 (JP)
	GPS	No	72 channels (GPS, Galileo, GLONASS, BeiDou), with Dead Reckoning					
	Wi-Fi / BLE	No			802.11a/b/g/n, BLE 4.2			
	Antennas (External)	No	1x SMA GNSS	1x SMA GNSS, 2x RP-SMA Wi-Fi/BT	1x SMA GNSS, 2x SMA Cellular, 2x RP-SMA Wi-Fi/BT			
OTHER	UPS	No	Internal Battery: 2000mA/h, Ni-MH (Factory Option: Li-ion)					
	RTC	Yes (Supercap)						
	Watchdog	Yes - Dedicated Chip						
	EEPROM	256kbit						
	TPM	TPM 2.0						
	Sensors	Temperature, Accelerometer						
	LEDs	1x Power, 1x Cellular, 2x Programmable						
	SIM Slot	No			2x Micro-SIM (User Accessible)			
POWER	Input	6-36VDC, with Surge, Noise, Reverse Polarity, Overvoltage and Short Protection, Vehicle Ignition Sense – Factory Option: Load Dump						
ENVIRONMENT	Operating Temp	- 40 to +85 °C						
	Storage Temp	- 40 to +85 °C						
CERTIFICATIONS	Regulatory	FCC, ISED, CE, JATE/TELEC			FCC, ISED		CE	JATE/TELEC
	Safety	EN 62368, UL 60950 (§)						
	Vertical	E-Mark, SAE/J1455(*)						
	Environmental	RoHS3, REACH						
	Wi-Fi / BT Radio	No		FCC, ISED, CE (RED)	FCC, ISED		CE (RED)	JATE/TELEC
	Cellular Radio	No			FCC, ISED, PTCRB, Verizon	FCC, ISED, PTCRB, AT&T	CE (RED)	JATE/TELEC
	Ingress	IP67						
MECHANICAL	Enclosure	Aluminum						
	Dimensions	178x183x62mm (WxDxH) - With Mounting Flange and Connectors						

### Software

<b>SOFTWARE</b>	OS	Eurotech Everywhere Linux
-----------------	----	---------------------------

(§) UL, NRTL listing Factory Option.

\* Factory Option

**Note:** The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.