



## Features

**Multicore i.MX6 SBC** - The CPU-351-13 offers configurations using single core, dual core or quad core technology to give to device manufacturers the right amount of processing power for their application

**Low Power** - The CPU-351-13 provides a large number of interfaces with a low power consumption in the order of 4W

**Connection-oriented** - Global cellular options, GNSS, Wi-Fi, Zigbee, Bluetooth 4.0 (with LE), and dual Gb Ethernet

**Natively Industrial** - Extended operating temperature, CAN bus interfaces, 3-axis accelerometer, integrated GNSS, and protected wide range power-in make the CPU-351-13 ideal for transportation and industrial applications

**Multiple Graphics** - The CPU-351-13 provides two video ports: LVDS and HDMI with integrated 4/5 wire resistive touch controller

**Power Management** - A on-board multi-chemistry battery charger simplifies the design of battery powered applications, and a smart power monitor allows to keep the power consumption beyond specified thresholds

**IoT Native** - The CPU-351-13 provides native support for IoT, including IoT middleware and access to Eurotech IoT Integration Platform

## Description

The CPU-351-13 is an iMX.6 Single Board Computer that delivers a large number of interfaces and peripherals while keeping the overall power consumption at a low 4W for typical applications.

Designed to be employed in a wide range of industrial and transportation applications, the CPU-351-13 provides key features such as 6-36VDC protected power in, CAN bus with optional J1939(CAN)/J1979(OBDII)/J1708 support and extended operating temperature.

With an on-board multi-chemistry charger, the CPU-351-13 simplifies the design of battery powered applications; an additional benefit comes from the integrated Smart Power Monitor, which can be used to keep the board within a user-defined power profile.

Support for cellular communications is available both on board and through the external Eurotech ReliaCELL 10-20 expansion module, which provides pre-certified, worldwide coverage.

The CPU-351-13 accelerates the development and deployment of IoT applications: it supports EC, the Eurotech Integration Platform for embedded devices. EC is a complete offering consisting of open field protocols, cloud-based resources like databases and brokers, and REST APIs.

The CPU-351-13 also supports [ESE](#), Eurotech Java-based framework for embedded devices. With ESF it is possible to develop portable applications in a fraction of the time thanks to high level, industry specific APIs.

To kickstart your projects and accelerate time to market, contact the Eurotech sales team to order a development kit.

## Specifications

<b>PROCESSOR</b>	CPU	NXP i.MX6, 1 to 4 cores, up to 1.2GHz
<b>MEMORY</b>	RAM	Up to 4GB DDR3 Soldered-down
<b>STORAGE</b>	Embedded	Up to 64GB eMMC Soldered Down (4GB Standard Version)
	SATA	1x SATA 2.0 (i.MX6Dual and i.MX6Quad Only)
	Other	1x microSD Slot
<b>I/O INTERFACES</b>	Ethernet	2x 10/100/1000Mbps
	USB	3x USB 2.0 (Type A), 1x USB 2.0 (Internal Header)
	Serial	2x RS-232/RS-422/RS-485 (DB9), 2x RS-232 (Optional)
	CAN bus	1x CAN bus – J1939(CAN)/J1979(OBDII)/J1708 (Contact Factory)
	Digital I/O	8x Isolated GPIO (with support for a 4x4 Key Pad)
	Analog I/O	2x Analog Voltage In
	Video	1x LVDS, 1x RGB, 1x HDMI (Optional) – 4/5 Wire Resistive Touch Controller: 3x Analog Video Inputs (Contact Factory)
	Audio	Analog Audio In/Out
	PCI Express	1x Mini PCIe Slot
	I2C	Yes
SPI	Yes	
<b>OTHER</b>	Battery	Multi Chemistry Battery Charger: Li-ion/Polymer, LiFePO4 – Factory Option: Lead Acid
	Sensors	3-axis Accelerometer
<b>POWER</b>	Input	6 to 36VDC Power In (5VDC Optional)
	Consumption	4W Typ.
	Management	Smart Power Monitor
<b>ENVIRONMENT</b>	Operating Temp	- 20 to +85°C or - 40 to +85°C (Depending on Specific CPU Version)
	Storage Temp	- 40 to +85°C
	Humidity	95% Relative at + 45°C Non-condensing
<b>CERTIFICATIONS</b>	Environmental	RoHS2, REACH
<b>MECHANICAL</b>	Dimensions	102x153mm (LxW)
<b>SOFTWARE</b>	OS	Support for Linux (Yocto), WEC2013
	IoT Framework	Everyware Software Framework, Everyware Cloud Ready

**Note:** The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.