



- ReliaGATE Expansion Module for LoraWAN
- EU and NA Bands
- Long Range (15 km/10 miles)
- Thousands of End-Point Nodes
- ISM Band Scan
- Industrial Grade
- Open Platform



## Features

**ReliaGATE Expansion Module for LoRaWAN** - Designed to be a companion for the ReliaGATE 10-12, expands the gateway capabilities with LoRaWAN connectivity

**EU and NA Bands** - Supports global deployment with European 868MHz (863-870MHz) and North American 915MHz (902- 928MHz) bands

**Long Range** - Covers long distances: high power radio with 15km / 10miles line of sight range (2km / 1.5miles in urban conditions); European ISM transmit power / duty-cycle limitations are supported

**ISM Band Scan** - Provides optimal performance: allows end node frequency change to improve interference rejection and dynamic link rate adaptation

**Industrial Grade** - Compact and sturdy, with reliable terminal block interfaces and a wide operating temperature range

**Open Platform** - Supported by Everyware Software Framework (ESF), the IoT Java/OSGi based-middleware for IoT Edge Gateways that accelerates gateway development and enables remote management

## Description

The ReliaWAN 10-12 is an expansion module that adds LoRaWAN capabilities to the [ReliaGATE 10-12](#).

Based on the Semtech SX1301 data concentrator, a multi-channel high performance transmitter/receiver, the ReliaWAN 10-12 is the fastest way to bridge a LoRaWAN with any cloud application; it is fully compatible with existing LoRaWAN infrastructures.

The ReliaWAN 10-12 is an industrial grade device that supports wide temperature range (-20 to +70°C) and comes in an impact-resistant ABS enclosure. Its compact design ensures simple deployment even in the most space-constraint applications.

The ReliaWAN 10-12 is a global device that supports European and North American ISM bands; its long range radio reaches up to 15km / 10miles in unobstructed applications. In difficult environments, such as urban areas with multiple building its penetration reaches a radius of 2km / 1.5miles.

Robust interference rejection and dynamic link rate adaptation dramatically improve performance in crowded networks; further efficiency is provided by the Listen Before Talk protocol, which allows multiple users on the same channel.

The ReliaWAN 10-12 is supported by [Everyware Software Framework \(ESF\)](#), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/OSGi middleware for IoT gateways.

Distributed and supported by Eurotech, ESF adds advanced security, diagnostics, provisioning, remote access and full integration with [Everyware Cloud \(EC\)](#), Eurotech's IoT Integration Platform (separately available).

### Ordering code: REWAN-10-12-xx

XX		- 01	- 02
<b>PROCESSOR</b>	Data Concentrator	Semtech SX1301	
<b>I/O INTERFACES</b>	Exp. Connector	Yes, for Side Expansion Modules	
<b>RADIO INTERFACES</b>	LoRa Bands	European 868MHz (863-870MHz)	North American 915MHz (902-928MHz)
	Transmission Power	- 6 to 25 dBm	- 6 to 27 dBm
	Receiver Sensitivity	-140 dBm Max	-137 dBm Max
	Antennas (External)	1x RP-SMA	
<b>POWER</b>	Consumption	3W Max	
<b>ENVIRONMENT</b>	Operating Temp	-20 to +70°C	
	Storage Temp	-40 to +85°C	
<b>CERTIFICATIONS</b>	Regulatory	CE	FCC, ISED
	Safety	EN 62368, UL 60950 (§)	
	Environmental	RoHS2, REACH	
	ISM Radio	CE (RED)	FCC, ISED
	Ingress	IP40	
<b>MECHANICAL</b>	Enclosure	Material: ABS - Color: Aluminum	
	Dimensions	96x21x45mm (LxWxH) - With Connectors	

### Software

<b>SOFTWARE</b>	IoT Framework	Everyware Software Framework (Java/OSGi)
-----------------	---------------	--

(§) UL, NRTL listing Factory Option.