



- GPU Accelerated
- Multiple Camera Input
- High Speed Interfaces
- Rolling Stock & Automotive
- Rugged
- Customizable

Features

GPU Accelerated - Powered by NVIDIA Jetson Xavier NX with up to 21 TOPS of GPU accelerated computing

Multiple Camera Input - Supports high speed, high frame rate cameras on GMSL, GbE and USB3

High Speed Interfaces - Provides best in class interfaces, like 3x GbE, 4x GMSL, USB3.1 G2 and Wi-Fi 6

Rolling Stock & Automotive - Certified for EN50155, EN45545 and E-Mark, supporting GNSS with Untethered Dead Reckoning

Rugged - Comes with rugged connectors, EN50155 OT3 operating temperature and with a 24-110VDC EN50155 power supply

Customizable - Personalization and full customization options are available, ranging from branding ("skins" and color) to deep HW/SW configurations

Description

The BoltGPU 10-31 is a rugged subsystem that has been designed to deliver GPU acceleration to Rolling Stock and Automotive applications.

Based on NVIDIA Jetson Xavier NX, it combines a 6-core, high-performance ARM CPU with a 384-core GPU and 48 Tensor Cores, offering exceptional power efficiency and up to 21 TOPS of accelerated computing.

The BoltGPU 10-31 is a power efficient, stand-alone unit that enables traditional and GPU-accelerated workloads in harsh environments, and comes with Automotive and Rolling Stock certifications, such as EN50155, EN45545 and E-Mark.

With a very complete set of high-speed interfaces, the BoltGPU 10-31 can be used to process multiple video streams from high speed, high frame rate cameras: it provides 3x GbE, 4x GMSL and 3x USB3.1 Gen 2 ports (noise and surge protected) that can be used to connect sensors and to create sophisticated networking architectures. Wireless connectivity is also cutting edge, thanks to Wi-Fi 6, BT5.1 and support for optional LTE modems.

The BoltGPU 10-31 offers plenty of storage capacity for video and other data via an internal NVME unit; removable storage is also supported via a microSD interface.

On-vehicle features include isolated CAN-FD and opto-isolated DIO, a GNSS with Untethered Dead Reckoning (optionally RTK), and rugged M12 connectors.

Other transportation and heavy-duty enablers are a wide range power input (24-110VDC, EN50155) with ignition sense and EN50155 OT3 operating temperature range (-25 to +70°C).

The BoltGPU 10-31 shares the same form factor of the BoltGATE 20-31 and of its expansion modules, making it possible to create hybrid architectures with extra features.

For customers seeking a tailored product, Eurotech offers a range of personalization and full customization options, ranging from branding ("skins" and color) to deep HW/SW configurations.

Ordering Code: BTGPU-10-31-XX

| XX | | -21 | -24 |
|-------------------------|------------------------------|--|--|
| NVIDIA MODULE | Core | NVIDIA® Jetson Xavier NX™ | |
| | CPU | 6-core NVIDIA Carmel ARM® v8.2 64-bit CPU 6MB L2 + 4MB L3 | |
| | GPU | 384-core NVIDIA Volta™ GPU with 48 Tensor Cores | |
| MEMORY | RAM | 8 GB 128-bit LPDDR4x @1600MHz, 51.2GB/s | |
| STORAGE | Embedded | 16 GB eMMC 5.1 | |
| | NVME | No | 512GB on M.2 Key M |
| | Additional Storage | Micro SD Slot (User Accessible) | |
| I/O INTERFACES | Ethernet | 3x 10/100/1000 Mbps - M12 | |
| | USB 3.0 | 2x Host USB3.1 Gen.2 (Noise and Surge Protected) - Type A | |
| | Serial | 1x TTL Serial Console | |
| | CAN | 1x CAN-FD (Isolated) - DB9 | |
| | Digital IO | ,2x Digital Inputs Optoisolated 2x Digital Outputs Optoisolated | |
| | Video OUT | 1x Video Output (Display Port) | |
| CAMERA INPUT | Camera IN | 4x GMSL (1.5Gbps to CSI-2) | |
| RADIO INTERFACES | Wi-Fi/BT Radio | No | Wi-Fi6 (802.11ax/ac/abgn) + BT 5.1/BLE |
| | Cellular Radio | Factory Option | |
| | GNSS | No | Internal (72 channels BeiDou, Galileo, GLONASS, GPS, QZSS) - Untethered Dead Reckoning (RTK GNSS - Factory Option) |
| EXPANSIONS | M.2 Key B (3042, 3052) | 1x M.2 Key B (USB3.1, USB2, PCIe x1) | |
| | M.2 Key E (1630, 2230, 3030) | 1x (PCIe x1, USB2.0, SDIO, I2C, I2S) - Used for Wi-Fi/BT | |
| | M.2 Key M (2242, 3042, 2280) | 1x (PCIe x4) - Used for NVME | |
| | Side Connector | PCIe x4 Endpoint Mode + 12V Power Input - PCIe x4 Shared with M.2 Key M | |
| OTHER | RTC | Yes (SuperCAP Backed) with Anti-tampering Timestamp | |
| | Discrete Watchdog | Yes | |
| | Serial EEPROM on I2C | 256 Kbit | |
| | TPM | Internal TPM 2.0 | |
| | Sensors | Internal Temperature | |
| | LED | 1x Power (Blue) 1x Cellular Activity (Green) 4x User Configurable (2x Green, 2x Amber) | |
| MISC | Buttons | 1x Reset | |
| | Anti-Tamper Detection | Yes | |
| | SIM Slot | Yes (User Accessible) | |
| POWER | Power Input | Wide Range 24-110VDC nom.(EN50155 Compliant); 24VDC Automotive (Regulation 10 Compliant) with Ignition sense | |
| | Power Consumption | TBD | |
| ENVIRONMENT | Operating Temperature | EN50155 OT3 | |
| | Storage Temperature | -40°C to +85 °C | |
| | Humidity | RH 5..95% Operating Non-condensing (40°C) | |
| CERTIFICATIONS | Regulatory | CE, FCC, ISED | |
| | Safety | CE, FCC, ISED | |
| | Vertical | EN50155, EN45545, E-Mark | |
| | Environmental | ROHS3, REACH | |
| | Wi-Fi/BLE Radio | No | RED, FCC, ISED |
| | Cellular Radio | No | |
| | Ingress Protection | IP 40 | |

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.

§ UL, NRTL listing Factory Option