



- Industrial Grade
- ReliaGATE Compatible
- 4x Isolated Digital Inputs
- 4x Isolated Digital Outputs
- 4x Protected Analog Inputs
- Open Platform
- Customizable



Features

Industrial Grade - Compact and sturdy, with reliable terminal block interfaces and a wide operating temperature range

ReliaGATE Compatible - Designed to be a companion for the ReliaGATE 10-12, expands the gateway capabilities with extra digital and analog ports

4x Isolated Digital Inputs - Supporting 0-36V input range and optionally customizable 0/1 level threshold

4x Isolated Digital Outputs - Open drain output transistors rated 60V, up to 0.5A output and clear LED status indication

4x Protected Analog Inputs - Supporting 0-36V input range and 12bit @1KHz sampling

Open Platform - Supported by Everyware Software Framework (ESF), the IoT Java/OSGi based-middleware for IoT Edge Gateways that accelerates gateway development and enables remote management

Customizable - Personalization and full customization options are available, ranging from branding ("skins" and color) to deep HW/SW configurations

Description

The ReliaIO 10-12 is a fast and simple way to expand the capabilities of Eurotech Multi-service IoT Edge Gateways with extra digital and analog ports.

Designed to be fitted to the side of the ReliaGATE 10-12, it is rated for the same level of reliability and operating temperature range.

The ReliaIO 10-12 features a high performance 32bit MCU to offload the gateway, delivering highly consistent performance under any load.

The digital section of the ReliaIO 10-12 supports 4x isolated digital inputs and 4x isolated digital outputs, while the analog section provides 4x protected analog inputs.

The ReliaIO 10-12 is supported by [Everyware Software Framework \(ESF\)](#), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/ OSGi middleware for IoT Edge Gateways.

Distributed and supported by Eurotech, ESF adds advanced security, diagnostics, provisioning, remote access and full integration with [Everyware Cloud \(EC\)](#), [Eurotech IoT Integration Platform](#) (separately available).

The ReliaIO 10-12 can be personalized and customized for additional capabilities through Eurotech Professional Services.

Ordering code: REIO-10-12-01

PROCESSOR	MCU	STM 32F072XX - 32 bit ARM Cortex M0
MEMORY	RAM	16KB SRAM with Hardware Parity
STORAGE	Embedded	128KB Flash
I/O INTERFACES	Digital Input	4x Digital Input Ports – 0-36V Input Range, 5kV (2.7kV RMS) Optoisolation, 0-1V Low Level Voltage, 2-36V High Level Voltage, 1V/2V 0/1 Level Threshold (Customizable as Factory Option)
	Digital Output	4x Digital Output Ports – 5kV (2.7kV RMS) Optoisolation, 60V Open Drain Output Transistors, 0.5A MOSFET AC/DC Output (with 0.5A Fuses)
	Analog Input	4x Analog Input Ports – 0-36V Input Range, 12bit Sigma Delta ADC Conversion, 1kHz Max Sampling Frequency, Input Protection Circuitry (5kV DC). Factory Option: 4-20mA Current Loop Compatibility
	Other Input	Factory Options: 3x PWM Programmable Inputs, 1x Odometer Mode, 1x Phase Angular Encode Mode. All Optional Inputs with Optoisolation: 5kV (2.7kV RMS)
OTHER	LEDs	4x Digital Output Status, 2x Programmable
POWER	Input	Provided by ReliaGATE 10-12
	Consumption	0.3W Typ.
ENVIRONMENT	Operating Temp	- 25 to +85°C
	Storage Temp	- 40 to +85°C
CERTIFICATIONS	Regulatory	CE, FCC, ISED
	Safety	EN 62368, UL 60950 (§)
	Environmental	RoHS2, REACH
	Ingress	IP40
MECHANICAL	Enclosure	Material: ABS - Color: Aluminum
	Dimensions	90.4x43.7x58 mm (LxWxH)

Software

SOFTWARE	IoT Framework	Everyware Software Framework (Java/OSGi)
-----------------	---------------	--

(§) UL, NRTL listing Factory Option.