



- **EN50155 Qualified**
- **Rugged and Compact**
- **Based on Intel® Atom™**
- **Specialized High Transmit Power Wi-Fi**
- **Low Power and Fanless**
- **IoT Ready**
- **ESF and EC Ready**

Features

Rugged and Compact - The BoltCOR 20-11 is very powerful, yet compact mobile computer. With extended temperature range and rugged circular connectors, it is the ideal platform for harsh environments both in mobile and industrial applications

Certified to Perform - Designed to meet the transportation market requirements, the BoltCOR 20-11 is EN50155 compliant and supports features such as opto-isolation on I/O and transient and surge protection on the wide range power supply

Connected Flexibility - The BoltCOR 20-11 features a high transmit power Wi-Fi interface ideal for fleet management, logistics, and mobile mesh networking applications. Additionally, a variety of 3G/4G cellular wireless options are available (consult factory).

Low Power and Fanless - Designed with high efficiency in mind, the BoltCOR 20-11 delivers exceptional performance and low power consumption

IoT Ready - Ideally suited for Industrial & Rugged IoT applications to connect data with the business enterprise to make intelligent and actionable decisions

ESF & EC Support - Available with Everyware Software Framework (ESF) to speed up application software development on the device. Also, enjoy the benefits of the Everyware Cloud (EC) to dramatically cut Time-to-Market when building scalable, robust applications that int

Description

The BoltCOR 20-11 is a rugged mobile computer platform that targets demanding vehicle and industrial installations such as those in heavy industry machinery, rail networks and rolling stock, buses, etc. Thanks to the very compact yet rugged design and integration, the system withstands the mechanical and temperature stresses encountered in harsh environmental conditions while providing an exceptional set of communication options needed in diverse use cases.

The BoltCOR 20-11 provides the computational power of the Intel Atom processor, connectivity through a specialized high transmit power Wi-Fi (standard) and 3G cellular (optional) networks, dual Gigabit Ethernet, a high performance GPS, and plenty of transportation-specific features such as optoisolated I/Os, serial ports, USBs and a wide range power supply.

Being low power, fanless, and compact, the BoltCOR 20-11 is off-the-shelf ready for integration in industrial, railway, automotive and similar applications. In addition, the device is IP65 protected and features high-end rugged connectors making the BoltCOR 20-11 easy to maintain and providing long term reliability in harsh environments.

The BoltCOR 20-11 can leverage Everyware Software Framework (ESF) for fast and reliable device application development and the Everyware Cloud (EC) that provides the entire infrastructure to instantly integrate devices and data into the business enterprise.

Specifications

PROCESSOR	CPU	Intel Atom Z510P, 1.1GHz
MEMORY	RAM	1GB RAM Soldered on Board
STORAGE	SSD	2GB Flash Disk SSD, 8GB DOM
	Other	1x microSDHC Slot (Maintenance)
I/O INTERFACES	Ethernet	2x 10/100/1000Mbps
	USB	3x USB 2.0 (Maintenance)
	Serial	1x RS-232 (Full-Duplex) – 1x RS-232/RS-422/RS-485 (RS-232/RS-422 Full-Duplex, RS-485 Configurable) – 1x RS-232 (Maintenance)
	CAN	2x CAN bus
	Digital I/O	2x Opto-isolated Digital Input – 1x Opto-isolated Digital Input Odometer
	Video	1x VGA (Maintenance)
RADIO INTERFACES	Cellular	GPRS, CDMA 1xRTT, EV-DO Rev. A, LTE (Consult Factory)
	GPS	50 channels Galileo
	Wi-Fi	Dual Band 2.4/5.0GHz IEEE 802.11 a/b/g/n - High TX Output Power up to 25dBm @ a/g/n Bands
	Antennas (External)	1x SMA GPS, 2x SMA Wi-Fi, 1x Reserved
OTHER	RTC	Yes (24 Hours at 25°C Typical)
	LEDs	4x Green LEDs
	Buttons	1x Reset
	SIM Slot	1x SIM Card Slot
POWER	Input	9 - 36VDC (Nominal 24VDC), Ignition Key Input
	Consumption	19W Typical
ENVIRONMENT	Operating Temp	- 30 to +60°C EN50155 Class T1 (70°C for 10 min)
	Storage Temp	- 40 to +85°C
	Humidity	< 95% Relative Humidity at +45°C Non Condensing
CERTIFICATIONS	Compliance	Design Qualified to the Following Certifications: EN 50155 (Railway Applications) – EN 61373 (Vibrations & Shocks) – EN 60950 (Safety) – EN 61000 (Burst Immunity Test) – EN 60068 (Temperature Test) – DIN-5510-2 (German Fire and Smoke) and ISO-11170 (Italian Fire and Smoke) – Load Dump (for 24V In): ISO 7637-2 (2004-06) – AREMA Class C Operating Temperature requirements – UL 60950-1, CSA C22.2 No. 60950-1
	Ingress	IP65
MECHANICAL	Enclosure	Black Ultra-light Extruded Aluminum Alloy Enclosure
	Dimensions	254x129x57mm / 10.0x5.08x2.24 in (LxWxH)
	Cooling	Fanless Design (No Moving Parts)
	Weight	1.5Kg
SOFTWARE	OS	Windows Embedded Standard 2009 Support