



- **Reliable Performance**
- **Integrated 3G/LTE Cellular**
- **Truly Industrial**
- **Field Protocol Support**
- **Cloud Certified**
- **Open Platform**
- **Customizable**



Features

- Reliable Performance** - Powerful and efficient: single, dual and quad core Intel Atom E3800, soldered-down eMMC storage and ECC memory for additional protection
- Integrated Cellular** - Certified 3G/LTE cellular modems can be integrated. It also supports Eurotech ReliaCELL 10-20, the cellular module with global carrier precertifications
- Truly Industrial** - Extended operating temperature, a wide range power supply with surge and sag protection, isolated and protected DIO, protected USB and serial
- Field Protocol Support** - Native support for Modbus, S7 and OPC UA, the extensible, secure, and platform-independent industrial interoperability standard
- Cloud Certified** - Seamless integration with Eurotech Everyware Cloud, Microsoft Azure, Amazon Web Services IoT and other Cloud services
- Open Platform** - Provides a Java/OSGi gateway middleware, to free the developer from proprietary solutions
- Customizable** - Flexible: personalization and full customization options are available, ranging from branding ("skin" and color) to deep HW/SW configurations

Description

The ReliaGATE 20-25 is a high-performance, globally certified, Multi-service IoT Edge Gateway for industrial and lightly rugged applications. It features up to four cores, soldered-down ECC RAM and storage, extended operating temperature support, wide range power supply, isolated and protected I/O interfaces, and customizable connectivity options.

The ReliaGATE 20-25 configuration options include GPS and LTE connectivity, both integrated and through the ReliaCELL 10-20 family of 2G/3G/LTE external modems with global carrier precertifications.

The ReliaGATE 20-25 comes with Everyware Software Framework (ESF), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/ OSGi middleware for IoT Edge Gateways.

Distributed and supported by Eurotech, ESF adds advanced security, diagnostics, provisioning and remote access. It supports ready-to-use field protocols (including Modbus, OPC-UA, S7), MQTT connectivity, web-based visual data flow programming and deep configuration.

ESF is also integrated with Everyware Cloud (EC), Eurotech's IoT Integration Platform (separately available), enabling advanced diagnostics, provisioning, and full remote device access and management.

The ReliaGATE 20-25 is Microsoft Azure certified and can also be integrated with 3rd party cloud services such as Amazon Web Services IoT.

Used stand-alone, or in conjunction with EC, the ReliaGATE 20-25 provides a fast go-to-market solution for projects of any size.

Ordering code: REGATE-20-25-xy

HARDWARE CONFIGURATION		-x2	-x3	-x4	-x5	-x6	-x7	-x8	
PROCESSOR	CPU	E3827, 1.75GHz, Dual Core		E3845, 1.91GHz, Quad Core		E3827, 1.75GHz, Dual Core		E3845, 1.91GHz, Quad Core	
	RAM	2GB, 1333MHz (DDR3L-ECC)		4GB, 1333MHz (DDR3L-ECC)		2GB, 1333MHz (DDR3L-ECC)		4GB, 1333MHz (DDR3L-ECC)	
STORAGE	Embedded	8GB eMMC							
	SATA	1x SATA 2.0 (Internal Connector) – 1x 32GB mSATA (Included on -4 Variants)							
	Other	1x microSD Slot (User Accessible)							
I/O INTERFACES	Ethernet	2x 10/100/1000Mbps - RJ45							
	USB	1x Host 3.0, 1x Host 2.0, 1x ReliaCELL (Noise and Surge Protected) - Type A							
	Serial	2x RS-232/RS-422/RS-485 (9 Wires, Noise and Surge Protected) on DB9 – 1x Serial Console TTL							
	CAN 2.0B	1x CAN bus with 5V (100mA) Power Out							
	Digital I/O	3x Digital Input 7 - 35VDC, 1KV Optoisolated – 3x Digital Output (40VDC), 20mA Sink							
	Video	1x Mini DisplayPort (Service Panel)							
	Audio	1x Line Stereo Line Out, 1x Stereo Mic In (Service Panel)							
EXPANSION	miniPCIe Slots	Up to 3x Full/Half Size Mini PCIe (PCIe/USB/mSATA)							
RADIO INTERFACES	Cellular	Eurotech ReliaCELL 10-20					LTE Cat 4 (EU) 2G/3G Fallback		
	GPS	Eurotech ReliaCELL 10-20 – Factory Option: Integrated GPS				GPS	Eurotech ReliaCELL 10-20 – Factory Option: Integrated GPS		
	Wi-Fi/ BT	No	b/g/n, BLE	No	b/g/n, BLE				
OTHER	RTC	Yes (User Accessible Battery)							
	Ext. Watchdog	Yes							
	Sensors	Temperature, Accelerometer							
	LEDs	1x Power, 3x miniPCIe Slot, 2x Programmable (Dual Color Green/Amber)							
	Buttons	1x Reset, 1x Programmable							
POWER	Input	7 - 35VDC (Nominal 24VDC), Surge and Sag Protection, Vehicle Ignition Input							
	Consumption	10W Idle		12W Idle		10W Idle		12W Idle	
ENVIRONMENT	Operating Temp	- 40 to +65°C							
	Storage Temp	- 40 to +85°C							
CERTIFICATIONS	Regulatory	CE, FCC, ISED							
	Safety	EN 62368, UL 60950 (S)							
	Environmental	RoHS2, REACH							
	Wi-Fi/ BT Radio	RED, FCC					RED		
	Cellular Radio	Eurotech ReliaCELL 10-20 Carrier Certifications					RED		
	IoT Platform	Microsoft Azure Certified							
	Ingress	IP30							
MECHANICAL	Enclosure	Material: Anodized Aluminium - Color: Aluminum							
	Dimensions	192x131x52mm (WxDxH)							

Ordering code: REGATE-20-25-xy

CONFIGURATION		-2y	-3y	-4y
SOFTWARE	OS	Eurotech Everyware Linux		Windows 10 IoT Enterprise
	SDK	Yocto-based Eclipse Tooling, Azul Java		-
	IoT Framework	-	Everyware Software Framework (Java/OSGi)	-

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.

(S) UL, NRTL listing Factory Option.