

# DynaCOR 44-11 - Edge AI and Data Acquisition

Versatile AI Server for Road Vehicle - 1 GPU, 2-bay Removable Storage, 2x 10GbE



- Versatile Acquisition and Processing
- Road Vehicles Grade
- Up to 18TFLOPS FP16 / 36TOPS INT8
- Intel Core i9, 10Gb/s Ethernet
- Dual Removable Storage Bays
- Compact and light
- Configuration Service

## Features

**Data Acquisition and Processing :** Designed for in-vehicle data acquisition and processing, with support for AI workloads and a range of factory options, such as vehicle buses (CAN, LIN), frame grabbers, etc.

**Designed for Road Vehicles :** Meets the most demanding requirements of Road Vehicle projects: selected components and rigorous testing to ensure reliable operation; automotive grade power supply with ignition key support for seamless on-board deployment

**Powerful Data Aggregation and Accelerated AI :** With an Intel Core i9 CPU, one NVIDIA® A2 GPU and dual 10GbE interfaces, supports a large variety of workloads, including general purpose computing, data logging, fusion and filtering

**Dual Removable Storage :** Two storage bays for 2.5" SATA drives that offer the convenience of easy access and removal; RAID 0/1 to provide the speed and reliability required for intensive data ingestion

**Simple to Deploy :** Extremely compact to fit easily in dense installations; with user accessible filters to protect the system from airborne pollutants; custom mounting options to simplify the development in the vehicle and to provide additional protection from shock and vibration

**Configuration Service :** Highly modular design, allows for personalized configurations, ranging from personalization (branding, color) to deeper customization, to match complex project requirements

## Description

The DynaCOR 44-11 is a versatile platform that offers a very balanced combination of computational performance, storage capacity and network bandwidth for in-vehicle workloads that include data acquisition and fusion, AI inference and data logging.

Designed for road vehicles, it offers reliable operation thanks to automotive grade ruggedization and an automotive power supply. Very compact and power efficient, the DynaCOR 44-11 can be deployed in dense installations; an optional mounting accessory further increases resilience to shock and vibration. User-serviceable filters offer the convenience of protection from airborne pollutants, such as dust and exhaust particulate, which are often found in road applications.

The DynaCOR 44-11 features a top-of line Intel Core i9 CPU rated at 35W, to deliver power efficient computational crunch, and provides AI acceleration thanks to a high-end NVIDIA® A2 GPU. Connection to the vehicle IP network and sensors is enabled by two 10GbE and two GbE interfaces; use cases requiring interfaces towards the low-level vehicle bus (such as CAN/CAN-FD, FlexRay, LIN, etc.) are optionally available as a Professional Service.

The DynaCOR 44-11 is also a capable storage server, supporting two removable bays for 2.5" SATA drives in RAID 0/1 configurations to provide high speed data recording and to offer extra protection to valuable information.

The DynaCOR 44-11 comes with [Everyware Software Framework \(ESF\)](#), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/OSGi middleware for IoT Edge Gateways. Distributed and supported by Eurotech, ESF supports ready-to-use field protocols (including Modbus, OPC-UA, S7), MQTT connectivity, web-based visual data flow programming and deep configuration. ESF is also integrated with [Everyware Cloud \(EC\)](#), Eurotech IoT Integration Platform (separately available), enabling advanced diagnostics, provisioning, and full remote device access and management.

Eurotech configuration management service allows fine tuning the DynaCOR 44-11 to meet and exceed your project requirements; examples of personalized configurations include customer branding (with custom logo and colors) and can go to deep customization with a range of option for project specific requirements (such as grabbers, choice of internal components, etc.): call us for more information on configuration management options.

**Note: The information in this document may be subject to change without notice and should not be construed as a commitment by Eurotech. While responsible precautions have been taken, Eurotech assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are property of their respective companies**

# DynaCOR 44-11 - Edge AI and Data Acquisition

Versatile AI Server for Road Vehicle - 1 GPU, 2-bay Removable Storage, 2x 10GbE

Ordering Code: DYCOR-44-11-XX		
	XX	-01
<b>PROCESSOR</b>	CPU	Intel Core™ i9-10900T 10 Cores / 20 Threads, 1.90GHz / 4.60GHz; Turbo Mode Off
<b>AI ACCELERATION</b>	GPU	1x Nvidia® A2
	TP32 Tensor Core	9 TFLOPS; 18 TFLOPS (Sparsity)
	BFLOAT16 Tensor Core	18 TFLOPS; 36 TFLOPS (Sparsity)
	FP16 Tensor Core	18 TFLOPS 36; TFLOPS (Sparsity)
	INT8 Tensor Core	36 TOPS; 72 TOPS (Sparsity)
	INT4 Tensor Core	72 TOPS; 144 TOPS (Sparsity)
<b>MEMORY</b>	RAM	64GB DDR4
<b>STORAGE</b>	OS Disk	500GB MLC NVME
	Data	4TB TLC (2x 2.5" SATA) RAW; 2x Bays
	RAID	RAID 0/1 Software
<b>I/O INTERFACES</b>	Ethernet	2x 10GbE (RJ45), 2x 1GbE (RJ45)
	Timing Support on Ethernet	IEEE 1588 PTP
	USB	6x USB 3.2 Gen 1 (Type A); 2x USB 2.0 (Type A)
	Serial	2x RS-232/422/485 (DB9 Connector)
	Vehicle Bus	CAN/ CAN-FD, FlexRay, LIN, others (Factory Option)
	Frame Grabber	Factory Option
	Video Out	1x HDMI v1.4b; 1x DisplayPort v1.2; 1x DVI-D
	Audio	1x Line-in, 1x Line-Out, 1x Mic-In
<b>RADIO INTERFACES</b>	Internal Cellular	Factory Option
	SIM Slot	Factory Option
	GNSS	Factory Option
	Wi-Fi/BT	Factory Option
	Ext. Antennas	Factory Option
<b>CYBERSECURITY (HARDWARE)</b>	TPM	TPM 2.0 Support
<b>EXPANSIONS</b>	Internal Expansion	1x M.2 2230 Key E (CNV), 1x M.2 2280 Key M (NVME), 4x SATA III; Expansion Availability Depends on Product Configuration
<b>COOLING</b>	Technology	Air Cooling
<b>POWER</b>	Input	Automotive Grade: 11 - 30VDC; 250Watt
<b>ENVIRONMENT</b>	Operating Temperature	0 to +50°C
	Storage Temperature	-20 to +70°C
	Humidity	10 to 90% Relative Humidity (Non-condensing) at +40°C
<b>CERTIFICATIONS</b>	IoT Platform	Azure IoT Certified, AWS Certified
	Regulatory	EU/UK: CE, UKCA; North America: Factory Option; Japan: Factory Option; Other Countries (Factory Option)
	Cellular	Factory Option
	Safety	Low voltage safety (2014/35/EU); EN 62368, UL 62368 (S)
	Environment	RoHS3, REACH
	Ingress Protection	IP20
<b>MECHANICAL</b>	Enclosure	Material: Metal; Color: Black
	Dimensions	215 x 131 x 300 mm (W x H x D), Excluding Antennas

S UL, NRTL listing Factory Option.

**Note: The information in this document may be subject to change without notice and should not be construed as a commitment by Eurotech. While responsible precautions have been taken, Eurotech assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are property of their respective companies**

# DynaCOR 44-11 - Edge AI and Data Acquisition

Versatile AI Server for Road Vehicle - 1 GPU, 2-bay Removable Storage, 2x 10GbE

## SOFTWARE

SOFTWARE	OS	Windows 10/11; Linux (Ubuntu LTS)
	IoT Framework	Everyware Software Framework (Java/OSGi)

**Note: The information in this document may be subject to change without notice and should not be construed as a commitment by Eurotech. While responsible precautions have been taken, Eurotech assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are property of their respective companies**