



- Fanless EN50155 TX Class
- 19" 1U Rack-Mount Short-Depth
- Intel Xeon® E
- Internal, Removable and RAID Storage
- Gb Ethernet and LTE Cellular
- Configurable and Future-Proof
- Long-term Availability



## Features

**Fanless EN50155 TX Class :** Fanless, vent-free enclosure, certified for rolling stock in the TX temperature class with S2 power supply, suitable for any heavy duty application

**Compact :** 19" 1U rack-mount with short-depth form factor to fit in most space-constrained on-board and track-side installations

**Scalable Performance :** Supports the intensive computation of media, data, network and storage-oriented workloads, through CPU options

**Flexible Storage :** Provides internal mSATA, fixed or removable 2.5" SSD/HDD disks with a rugged and locking tray design and RAID levels 0, 1

**Extended Connectivity :** Configurable with multiple simultaneous cellular modules, multiple SIMs, dual Gb Ethernet, Wi-Fi 2.4/5.0GHz, BLE, and GNSS with Untethered Dead Reckoning

**Configurable and Future-Proof :** Based on a modular architecture compliant with industry standards, like COM Express, PCIe and miniPCIe, enables fast customizations and compatibility to future technologies

**Long-term Availability :** Designed for markets and use cases where long-term availability and support is a must have requirement

## Description

The BoltCOR 30-17 is a fanless EN50155 certified server that is designed to exceed the requirements of rolling stock applications in the TX temperature class; it is extremely rugged and suitable for any project where consistent performance and reliability are a must.

With up to 32GB of DDR4 RAM (ECC option), soldered down CPUs, mSATA storage and a S2 class power supply, the BoltCOR 30-17 is extremely resilient; high reliability components, conformal coating, a vent-free design and a sturdy build add extra protection to a compact, 295mm deep, 1U rack-mount chassis.

Expandability options include two HDD/SSD drives, key-locked swappable storage bays, internal mSATA, a user-accessible SD slot and RAID levels 0, 1; additional peripherals can be added via four miniPCIe and one x16 PCIe slots.

The BoltCOR 30-17 features a wide range of radio and wireless capabilities, including cellular carrier pre-certified system configurations. Customization options include internal global cellular modems, multiple modem and SIM configurations, MIMO Wi-Fi, Bluetooth Low Energy, and GNSS with Untethered Dead Reckoning.

The BoltCOR 30-17 affords unprecedented system configurability: off-the-shelf configurations and build-to-order variants out of a palette of CPU, power supply, memory, storage and I/O subsystems options.

Designed for rolling stock applications, the BoltCOR 30-17 offers long term availability and support programs that ensure continuity of supply and customer service.

Ordering Code: BTCOR-30-17-XX

	XX	-31*	-41*
<b>PROCESSOR</b>	CPU	Xeon E3-1505L v6 2.2GHz (3.0GHz), Quad Core, 25W TDP	
<b>MEMORY</b>	RAM	16GB DDR4 ECC Factory Option: up to 32GB DDR4 ECC or non-ECC	
<b>STORAGE</b>	SATA	2x 512GB SSD Factory Option: up to 2 x 1TB SSD	
	Embedded	1x 64GB mSATA Factory Option: up to 128GB mSATA	
	Drive Bay	1x Removable Drive Bay for up to 2x 2.5" SATA Drives with key-lock mechanism	
	RAID	Software RAID 0, 1 (Factory Option: HW RAID Controller)	
	Other	1x SDHC/SDXC Card Slot (UHS-1 50MB/s max) (Service Panel)	
<b>I/O INTERFACES</b>	Ethernet	2x 10/100/1000Mbps Auto Sensing IEEE 1588; M12 Xcoded Connector Factory Option: up to 3x 10/100/1000Mbps	
	USB	2x Host 2.0 Noise and Surge Protected (Service Panel)	
	Serial	1x Serial Console TTL (Service Panel)	
	Video	1x MiniDisplayPort (Service Panel)	
<b>RADIO INTERFACES</b>	Cellular	LTE Cat 4 Global Modem Factory Option: 3x Modems	
	GNSS	Factory Option	
	Wi-Fi / BT	Factory Option (802.11 a/b/g/n, BLE 4.0)	
	Antenna (External)	2x SMA Cellular, 2x RP-SMA Wi-Fi/BT	
<b>EXPANSION</b>	miniPCIe	Up to 4x Full/Half Size Mini PCIe Slots (PCIe/USB/mSATA)	
<b>OTHER</b>	RTC	Yes, with SuperCAP (2 Months Retention @25°C)	
	Watchdog	Yes	
	EEPROM	32KByte	
	TPM	Factory Option: TPM 2.0	
	Sensors	Temperature (Inside the product); Factory Option: Accelerometer	
	LEDs	1x Power, 1x SATA Activity, 4x Programmable	
	SIM Slot	Up to 3x 2FF (Mini) Dual-SIM Support for up to 3x Modems	
<b>POWER</b>	Input	Nominal: 110Vdc isolated (EN 50155 S2) Range: 77 to 143Vdc (EN 50155 S2) Factory Options: 24, 48, 72Vdc	
	Consumption	80W Max	
<b>ENVIRONMENT</b>	Operating Temp	EN 50155 Class OT4 (-40 to +70°C), ST1 (10 minutes at +85°C)	
	Storage Temp	- 40 to +85°C	
<b>CERTIFICATIONS (*)</b>	Regulatory	CE; Factory Option: FCC	
	Vertical	EN50155, EN45545 (Fire and Smoke)	
	Safety	IEC/UL 62368-1	
	Environmental	RoHS3, REACH	
	Wi-Fi / BT Radio	RED; Factory Option: FCC	
	Cellular Radio	RED; Factory Option: FCC	
	Ingress	IP40	
<b>MECHANICAL</b>	Enclosure	Steel	
	Dimensions	483x313x44mm (WxDxH)	
	Weight	< 7Kg	
<b>SOFTWARE</b>	OS	Ubuntu 18.04 LTS	Windows 10 IoT Enterprise
	IoT Framework	ESF on Docker	

(S) UL, NRTL listing Factory Option.

\* Contact Eurotech for availability and other configurations

Note: The information in this document may be subject to change without notice and should not be construed as a commitment by Eurotech. While responsible precautions have been taken, Eurotech assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are property of their respective companies